



Not To Scale

NOTES:

1. ALL DIMENSIONS ARE IN MILLIMETRES UNLESS OTHERWISE SHOWN.
2. CARPARK CROSSFALL SHALL BE 2.5% UNLESS OTHERWISE APPROVED BY COUNCIL.
3. REFER TO CMAA PE01- PERMEABLE INTERLOCKING CONCRETE PAVEMENTS - DESIGN AND CONSTRUCTION GUIDE.
4. FOOTPATHS ARE TO BE CONSTRUCTED TYPICALLY AS PER COUNCIL STANDARD DRAWINGS SD- 03 & SD- 04.
5. KERBS AND CHANNELS ARE TO BE CONSTRUCTED AS PER COUNCIL STANDARD DRAWING SD- 02.
6. SHOULD WORKS ENCROACH OR HAVE POTENTIAL TO ENCROACH WITHIN TREE ROOT ZONES, PLEASE CONTACT COUNCIL FOR DIRECTION. NO TREES/ROOTS SHALL BE REMOVED OR TRIMMED, WITHOUT PRIOR APPROVAL OF COUNCIL'S ARBORIST.
7. THE APPLICATION AND EXTENT OF THIS TREATMENT SHALL BE DETERMINED BY THE REQUIREMENTS OF THE PROJECT.



THE CORPORATION OF THE CITY OF MARION

EDGE STRIP/ PERMEABLE PAVED CARPARK DETAIL

Drawn : E. O.

Date : 07 April 2022

Approved :

Last Revised : April 2022

Ref. No. : SD-32